



Firebird AW Hydraulic Oil

Firebird AW Hydraulic Oil is an environmentally responsible antiwear hydraulic oil formulated with a blend of high-quality conventional and re-refined base stocks. It is recommended for use in a wide variety of industrial, mobile and marine hydraulic system applications. The use of re-refined base stocks helps lessen the environmental impact of disposal of used oil.

Firebird AW Hydraulic Oil is formulated to provide excellent wear protection for hydraulic pumps and motors, and to protect hydraulic system components against rust and corrosion. It has good oxidation resistance at high temperatures to minimize deposit formation and provide long service life. It has good water-separating properties to minimize the formation of emulsions, and is resistant to excessive foam buildup that can cause poor or sluggish hydraulic system response.

Firebird AW Hydraulic Oil meets the performance requirements of all major hydraulic pump manufacturers, and is recommended for use in all types of high-pressure, high-speed hydraulic pumps.

Applications

- Hydraulic systems on industrial, mobile and marine equipment
- Automated machine tools
- Hydraulic elevators, hoists, presses and floor jacks
- Marine cargo winches and steering systems
- Mobile construction equipment
- Service station lifts
- Air tools and other pneumatic equipment lubricated through air line lubricators
- Chain drives
- Electric motor bearings

Firebird AW Hydraulic Oil meets the requirements of the following industry and OEM specifications:

- Denison Hydraulics HF-0, HF-1, HF-2
- DIN 51524 Part 2, Antiwear Hydraulic Oils, Type HLP
- German Steel Industry SEB 181222
- ISO 11158:1997, Family H (Hydraulic Systems), Type HM
- U.S. Steel 127
- Vickers (Eaton) M-2950-S, I-286-S

**Antiwear
Hydraulic Oil
Formulated With
Re-refined
Base Stocks**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**lubricants@
p66.com**



Features/Benefits

- Excellent wear protection for hydraulic pumps and motors
- Good oxidation resistance
- Protects against rust and corrosion
- Good water-separating properties
- Good foam resistance
- Good low-temperature properties for cold start-ups
- Lessens the environmental impact of used oil disposal

Firebird AW Hydraulic Oil

Typical Properties

ISO Grade	32	46	68
Specific Gravity @ 60°F	0.866	0.867	0.876
Density, lbs/gal @ 60°F	7.21	7.22	7.29
Color, ASTM D1500	1.0	1.0	3.0
Flash Point (COC), °C (°F)	210 (410)	235 (455)	245 (473)
Pour Point, °C (°F)	-31 (-24)	-30 (-22)	-27 (-17)
Viscosity,			
cSt @ 40°C	32.0	46.0	68.0
cSt @ 100°C	5.4	6.8	8.6
SUS @ 100°F	165	237	353
SUS @ 210°F	44.4	49.0	55.2
Viscosity Index	102	102	97
Acid Number, ASTM D974, mg KOH/g	0.40	0.40	0.40
Copper Corrosion, ASTM D130	1a	1a	1a
Demulsibility, ASTM D1401, minutes to pass	40	50	40
FZG Scuffing Test, ASTM D5182, Failure Load Stage	11	11	11
Oxidation Stability, TOST, ASTM D943-04a, hours	2,000	2,000	2,000
Rust Test, ASTM D665 A&B	Pass	Pass	Pass
Zinc, wt %	0.043	0.043	0.043
Re-refined Content, Finished Oil, vol %	56	56	56

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2013 Phillips 66 Company, Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.