

Firebird LD Motor Oil

76® Firebird LD Motor Oil is an environmentally responsible, part-synthetic automotive engine oil designed to provide excellent engine protection for gasoline-fueled and flex-fuel passenger cars and light trucks under all operating conditions. It is formulated with a blend of synthetic and high-quality re-refined base stocks. The use of re-refined base stocks helps lessen the environmental impact of disposal of used oil.

Firebird LD Motor Oil is formulated to provide excellent wear protection, to minimize sludge and varnish formation, and to resist viscosity and thermal breakdown, even in severe service. It also protects against rust and bearing corrosion, and is resistant to foaming. The part-synthetic formulation provides enhanced performance benefits at extreme temperatures compared with conventional engine oils, for extra protection under all driving conditions.

Firebird LD Motor Oil is fully licensed by the API and meets new car warranty requirements as defined by ILSAC GF-5. It meets “Resource Conserving” requirements for fuel economy improvement, emission system and turbocharger protection, and protection of engines operating on ethanol-containing fuels up to E85. It is backward serviceable for use where API SM or earlier “S” category engine oils are recommended.

Applications

- Gasoline-fueled and flex-fuel passenger cars, light trucks and sport utility vehicles

Firebird LD Motor Oil is licensed for:

- ILSAC GF-5
- API Service SN with Resource Conserving

Firebird LD Motor Oil meets or exceeds the requirements of:

- Chrysler MS-6395 (Rev. T)
- Ford WSS-M2C945-A (SAE 5W-20), WSS-M2C946-A (SAE 5W-30)
- GM6094M (obsolete)

Features/Benefits

- Meets ILSAC GF-5 requirements for new cars under warranty
- Friction-modified for improved fuel economy
- Resists viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation

**Synthetic Blend
Passenger Car
Engine Oil
Formulated With
Re-refined
Base Stocks**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**76lubricants@
p66.com**

- Protects against wear
- Protects against rust and bearing corrosion
- Good low-temperature pumpability for easier cold starts
- Good foam resistance
- Formulated to protect turbochargers and emissions control system catalysts
- Formulated for use in vehicles operating on ethanol-containing fuels up to E85
- Lessens the environmental impact of disposal of used oil

Firebird LD Motor Oil

Typical Properties

SAE Grade	5W-20	5W-30
Specific Gravity @ 60°F	0.866	0.866
Density, lbs/gal @ 60°F	7.21	7.21
Color, ASTM D1500	3.5	3.5
Flash Point (COC), °C (°F)	220 (428)	220 (428)
Pour Point, °C (°F)	-39 (-38)	-39 (-38)
Viscosity, Kinematic		
cSt @ 40°C	49.0	66.0
cSt @ 100°C	8.5	10.8
Viscosity Index	159	159
Cold Cranking Viscosity, cP @ -30°C	5,600	6,200
High-Temp/High-Shear Viscosity, cP @ 150°C	3.1	3.1
Sulfated Ash, ASTM D874, wt %	0.96	0.96
Total Base Number (TBN), ASTM D2896	8.0	8.0
Phosphorus, wt %	0.077	0.077
Zinc, wt %	0.085	0.085
Re-refined Content, Finished Oil, wt %	>50	>50

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.