





Special Bar & Chain Oil

Special Bar & Chain Oil is an adhesive lubricant developed to lubricate the chain, bar guide and drive sprocket on chain saws used in the logging industry. It is suitable for use with all types of chain saws equipped with either hand-operated or automatic oilers.

Special Bar & Chain Oil is formulated to provide good wear protection and resistance to foaming. It protects the chain, bar guide and drive sprocket against wear. A tackiness agent minimizes sling-off during chain saw operation.

Special Bar & Chain Oil is dyed red for easy visibility on the chain.

Applications

- Chain saws (bar guide, chain and drive sprocket)
- Industrial chain drives
- · Machine tool guides and slideways

Features/Benefits

- · Protects against wear
- Resists sling-off
- Good foam resistance
- Dyed red for easy visibility on the chain

Adhesive Chain Saw Lubricant

CONTACT

Phillips66 Lubricants.com

U.S. Customer Service:

1-800-368-7128

Technical Hotline: 1-877-445-9198

International Customer Service: 1-832-765-2500

E-mail address: lubricants@ p66.com







Special Bar & Chain Oil

Typical Properties			
Specific Gravity @ 60°F	0.877	0.878	0.904
Density, Ibs/gal @ 60°F	7.30	7.31	7.53
Color, Visual	Red	Red	Red
Flash Point (COC), °C (°F)	220 (428)	228 (442)	235 (455)
Pour Point, °C (°F)	-12 (10)	-10 (14)	-10 (14)
Viscosity,			
cSt @ 40°C	68.0	142	205
cSt @ 100°C	9.3	15.5	21.0
SUS @ 100°F	351	740	1,071
SUS @ 210°F	57.6	81.7	105
Viscosity Index	114	112	121
Foam Test, ASTM D892	Pass	Pass	Pass

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via http://w3apps.phillips66.com/NetMSDS.