



Spindle Oil

Spindle Oil is a high-quality spindle bearing oil developed for the lubrication of high-speed spindle bearings in machine tools and textile machinery.

Spindle Oil is formulated with an oiliness agent and/or an ashless antiwear additive plus select inhibitors to provide excellent lubricity and wear protection, protection against rust and corrosion, and resistance to foaming. It has excellent oxidation resistance and thermal stability at high temperatures to minimize deposits and provide long service life. It has excellent water-separating properties to minimize the formation of emulsions, and is resistant to excessive foam buildup. It is nonstaining for use in textile equipment.

Spindle Oils ISO VG 2, 6, 10 & 22 are recommended primarily for use in high-speed CNC milling machines, precision grinders and other machine tools. They meet the performance requirements of leading manufacturers of high-speed CNC milling machines. They also may be used in low-pressure hydraulic systems that require a low-viscosity oil.

Spindle Oil ISO VG 15 is recommended for lubrication of high-speed needle and spindle bearings in agricultural and textile machinery, such as spinning machines.

Applications

- Horizontal, vertical, bed-type, knee-type and turret-type CNC milling machines
- High-speed needle and spindle bearings in industrial, agricultural and textile machinery
- Low-pressure hydraulic systems that require a low-viscosity oil

Features/Benefits

- Excellent oxidation resistance and thermal stability
- Long service life for reduced operating and maintenance costs
- Protects against wear
- Excellent oiliness characteristics (ISO VG 2 & 15)
- Protects against rust and corrosion
- Excellent water-separating properties
- Excellent low-temperature performance
- Clear color
- Nonstaining
- Quick foam release

Spindle Bearing Oil

CONTACT INFORMATION

Phillips66
Lubricants.com

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
lubricants@
p66.com



Spindle Oil

Typical Properties

ISO Grade	2	6	10	15	22
Specific Gravity @ 60°F	0.806	0.833	0.848	0.852	0.856
Density, lbs/gal @ 60°F	6.71	6.94	7.06	7.09	7.13
Color, ASTM D1500	L 0.5	L 0.5	L 0.5	L 0.5	L 0.5
Flash Point (COC), °C (°F)	99 (210)	150 (302)	171 (340)	188 (370)	168 (335)
Pour Point, °C (°F)	-40 (-40)	-40 (-40)	-36 (-33)	-25 (-13)	-37 (-35)
Viscosity,					
cSt @ 40°C	2.1	5.1	10.0	15.1	22.1
cSt @ 100°C	1.0	1.7	2.6	3.4	4.4
SUS @ 100°F	33	44	61	83	115
SUS @ 210°F	29	32	35	38	41
Acid Number, ASTM D974, mg KOH/g	0.04	0.04	0.03	0.01	0.03
Copper Corrosion, ASTM D130	1a	1a	1a	1a	1a
For-Ball Wear, ASTM D4172, Scar Diameter, mm	0.52	0.49	0.42	—	0.41
Rust Test, ASTM D665 A&B	Pass	Pass	Pass	Pass	Pass

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company, Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.