



## Air Compressor Oil

Air Compressor Oil is a high-quality, non-detergent circulating oil developed primarily for use in older reciprocating air compressors. It also is recommended for use in other industrial applications where the equipment manufacturer specifies a non-detergent, ISO VG 100 mineral oil.

Air Compressor Oil is formulated to provide excellent oxidation resistance, rust and corrosion protection, and resistance to foaming. It has excellent oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life. It protects against rust and corrosion. It has excellent water-separating properties to minimize the formation of emulsions and is resistant to excessive foam buildup.

### ***Applications***

- Older reciprocating air compressors with low discharge temperatures
- Deep well water pump gear drives
- Vacuum pumps
- Lightly loaded enclosed industrial gear drives where an AGMA 3 (non-EP) oil is specified
- Industrial applications that require a non-detergent, ISO VG 100 oil

### ***Features/Benefits***

- Excellent oxidation resistance and thermal stability
- Protects against sludge and varnish formation
- Protects against rust and corrosion
- Excellent water-separating properties
- Good foam resistance
- Low carbon-forming tendency

## **Non-Detergent Air Compressor Oil**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**lubricants@  
p66.com**



## Air Compressor Oil

### Typical Properties

ISO Grade	100
Specific Gravity @ 60°F	0.868
Density, lbs/gal @ 60°F	7.23
Color, ASTM D1500	0.5
Flash Point (COC), °C (°F)	277 (531)
Pour Point, °C (°F)	-29 (-20)
Viscosity,	
cSt @ 40°C	100
cSt @ 100°C	11.3
SUS @ 100°F	522
SUS @ 210°F	65.0
Viscosity Index	99
Acid Number, ASTM D974, mg KOH/g	0.08
Copper Corrosion, ASTM D130	1a
Demulsibility, ASTM D1401, minutes to pass	10
Foam Test, ASTM D892	Pass
Rust Test, ASTM D665 A&B	Pass

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company, Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.