



Powerol Truck Tested Motor Oil, SAE 30

Powerol Truck Tested Motor Oil, SAE 30, is a high-quality diesel engine oil designed for use in older four-stroke cycle diesel engines that specify a monograde API Service CF or CD quality oil. It also may be used in some 2-stroke cycle diesel engines operating in cold climates, and in some heavy-duty manual transmissions in trucks and buses.

Power Truck Tested Motor Oil, SAE 30, is formulated to provide excellent wear protection, to minimize the formation of sludge and varnish, to protect against bearing corrosion, and to resist foaming. The low ash content helps minimize the formation of valve deposits and keep intake ports clean to maintain good power output in 2-stroke cycle applications.

Applications

- Older 4-stroke cycle diesel engines where the manufacturer specifies a monograde API CF or CD quality oil
- Some 2-stroke cycle diesel engines operating in cold climates
- Some heavy-duty manual transmissions in trucks and buses

Truck Tested Motor Oil, SAE 30, meets or exceeds the requirements of:

- API Service CF, CF-2 (obsolete)

**Low-Ash Diesel
Engine Oil**

Marc Nelson Oil Products

PO Box 7135 • Salem OR 97303 • (503) 363-7676 • (800) 523-7676
www.marcnelsonoil.com



Powerol Truck Tested Motor Oil, SAE 30

Typical Properties

SAE Grade	30
Specific Gravity @ 60°F	0.879
Density, lbs/gal @ 60°F	7.32
Color, ASTM D1500	L 4.0
Flash Point (COC), °C (°F)	240 (464)
Pour Point, °C (°F)	-33 (-27)
Viscosity, Kinematic	
cSt @ 40°C	92.0
cSt @ 100°C	11.0
Viscosity Index	115
High-Temp, High-Shear Viscosity, cP @ 150°C	3.6
Sulfated Ash, ASTM D874, wt %	1.0
Total Base Number (TBN), ASTM D2896	8.1
Zinc, wt %	0.109

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet.

Marc Nelson Oil Products

PO Box 7135 • Salem OR 97303 • (503) 363-7676 • (800) 523-7676
www.marcnelsonoil.com